

Armeringsnet B 550 B – EN 10080 – INF 165

Stødzonenet

Varekode	Alternativ betegnelse	Dimension i mm	Stritter Længdetr.	Stritter Tværtr.	Stødlængde	Dækkeevne	Kg/m ²	Kg/stk	Stk/bdt
JAVF5116	6010 Stz	5000x2350x100x6	410/90	300/90	347	9,2	3,930	46,20	30
JAVF5166	6015 Stz	5000x2350x150x6	510/140	410/140	347	8,78	2,560	30,08	50
JAVF5118	8010 Stz	5000x2350x100x8	510/90	460/90	462	8,55	6,749	79,30	10/20
JAVF5168	8015 Stz	5000x2350x150x8	510/140	560/140	462	8,1	4,387	51,55	30
JAVF5128	8020 Stz	5000x2350x200x8	610/190	560/190	462	7,92	3,251	38,20	30/40
JAVF5111	10010 Stz	5000x2350x100x10	610/90	660/90	578	7,48	9,893	116,24	10
JAVF5161	10015 Stz	5000x2350x150x10	660/140	560/140	578	7,61	6,729	79,07	20
JAVF5121	10020 Stz	5000x2350x200x10	610/190	560/190	578	7,7	5,077	59,66	20
JAVF5113	12010 Stz	5000x2350x100x12	710/90	660/90	693	7,1	14,060	165,21	10
JAVF5163	12015 Stz	5000x2350x150x12	660/140	710/140	693	7,13	9,307	109,36	10
JAVF5123	12020 Stz	5000x2350x200x12	810/190	760/190	693	6,72	6,752	79,34	10/20
JAVF6318	8010 Stz	6000x3000x100x8	575/25	575/25	462	13,75	6,913	124,43	15
JAVF6368	8015 Stz	6000x3000x150x8	575/25	575/25	462	14,06	4,674	84,14	20
JAVF6311	10010 Stz	6000x3000x100x10	675/25	675/25	578	12,96	10,489	188,80	10
JAVF6361	10015 Stz	6000x3000x150x10	725/25	725/25	578	12,96	6,993	125,87	10
JAVF6313	12010 Stz	6000x3000x100x12	775/25	775/25	693	12,19	14,652	263,74	7
JAVF6363	12015 Stz	6000x3000x150x12	875/25	875/25	693	11,81	9,620	173,16	10
JAVF6323	12020 Stz	6000x3000x200x12	975/25	975/25	693	11,44	7,104	127,87	15
JAVF6317	16010 Stz	6000x3000x100x16	1050/50	1050/50	924	10	23,700	426,60	4
JAVF6367	16015 Stz	6000x3000x150x16	1150/50	1150/50	924	9,65	15,537	279,66	4

Tabellen er opdateret 30.03.2023

Dækkeevnen for SZN-net er mindste værdi af enten (bredde-stød) x (længde-stød) eller dækarealet, når nettene udlægges så masker "passer".